



IBEX® 1000 P

Durable, Lightweight, Technician-tested and approved

Benefits

Adjusted settings from 50 to 125 lbs (25 to 55 kgs) allow a smooth confident climb every time

Robust, lightweight electrical control box – technician-tested

Easily retrofits in any wind turbine

Quick set up - click, plug and climb

Minimal maintenance



System Components

- Top Sheave Assembly
- 2 Motor Assembly with Junction Box
- 3 Portable Electrical Control Box
- 4 EasyClimb Controller
- 5 Round Reinforced Polymer Belt and Belt Guides
- 6 Rung Reinforcements

The new IBEX[®] 1000P climb assist system sets the standard for portability and affordability. Featuring a lightweight, compact portable control box, the 1000P delivers the intelligent performance and comfort that makes IBEX[®] the market leader globally.











Click, Plug & Climb

At only 8.5 lbs (4 kgs) and IP56 rated, the portable control box is compact and built to last.

Device use

- 1 Simply click the control box to its mounting bracket
- 2 Attach two quick-connect plugs
- 3 Turn on the switch, and climb

The EasyClimb Controller allows each user to customize his/her assistance from 50 to 125 lbs (25 to 55 kgs), and delivers constant load support regardless of climbing speed.



The world leader and pioneer in powered access solutions for over 60 years.



Power Climber Wind

We help major wind turbine OEMs, owners, and service providers manage their operation and maintenance costs by providing the most reliable access equipment and expertise to improve employee safety, productivity, and retention.

Americas

365 Upland Drive Seattle, WA 98188 USA +1 (206) 394-5306

Europe

Satenrozen 7 Kontich, Belgium 2250 +32 3-451 05 00

info@powerclimberwind.com www.powerclimberwind.com

Specifications

Power Supply: 120 or 220Vac 60 Hz 1ø

Motor: 90V PMDC 0.5HP

Belt: 10.5mm reinforced polymer

Environmental Rating: IP56

Corrosion Protection: Class 3

Noise level: 75 dBA

Temperature Range: -35C to +50C Operating -40C to +60C Storage

Amperage Draw: 10 maximum

Weight: 8.5 lbs (4 kgs)

CE

